

## Composite Pipe Repair PermaWrap & WeldWrap

## No Shutdown/ No Hot Work / No Heavy Equipment / MFL Detectable / Diamond Lock Technology

The patented PermaWrap<sup>™</sup> composite reinforcement sleeve is a pre-manufactured rigid composite pipe wrap with advantages that have a direct benefit to clients.

- PermaWrap<sup>™</sup> is magnetically detectable by MFL In-Line Inspection (ILI) tools eliminating post identification methods or procedures.
- The patented "diamond grip" embossment technology provides a mechanical lock system allowing individual layers of the wrap to nest within each other, even on inclines or in the vertical position. This feature virtually eliminates telescoping during application.
- Available in multiple widths: 6, 9, 12, 15 and 18 inches in diameters from 4 to 60 inches.
- WeldWrap<sup>™</sup>: The only composite repair sleeve designed for girth weld zone reinforcement



462, 11007 Jasper Ave. Edmonton, AB T5K 0K6 Office: **780.461.9393** Cell: **780.953.5820** Fax: **780.463.4386** info@avheng.com www.avheng.com



## Features

- Repair
  - External corrosion defects to 80% wall loss
  - Blunt pipeline dents and gouges
  - Girth weld repairs (WeldWrap)
  - Field bends and elbows
  - Vertical & horizontal pipeline
  - Corrosion or wear at pipe supports.

- Properties
  - $\circ$  Cure time 2 hours
  - Maximum operating temperature 72°C
  - Tensile strength 90,000 psi
  - Design life 50 years
- Compliance
  - $\circ$  ASME PCC-2
  - o ISO 24817
  - o CSA
  - o DOT

